

Commercial Product Data Sheet

Product Description

Pro Prep is a clear, blended solvent.

Product Uses

Pro Prep is used to clean the transition areas of in-place Parapro 123 Flashing System membranes and Terapro Waterproofing & Surfacing Membranes at tie-ins, repairs, and between staged coats of resin. Pro Prep is also used to prepare metal and plastic surfaces prior to application of Parapro 123 Flashing Systems. Pro Prep can be utilized for cleaning spills, tools, and equipment.

Packaging

Pro Prep is supplied in a 1-gallon (3.8 l), resealable metal F-style can.

Coverage

Consumption will vary depending upon application and use.

Storage

Always store in cool and dry location. Do not store in direct sunlight. Pro Prep is flammable. Keep away from heat, sparks, and open flame.

Application Conditions

Refer to the Parapro Membrane Resin, Pro Primer R, Pro Primer W, and Terapro Base Resin product data sheets for recommendations on specific applications.

Application

Pro Prep should be applied using clean shop rags or cloth. After cleaning, the solvent should be allowed approximately 20 minutes to evaporate. The next application process should follow within 60 minutes.

Pot Life & Drying Time

Pro Prep requires approximately 20 minutes drying time.

Safety Recommendations

Refer to the Pro Prep Material Safety Data Sheet (MSDS) prior to use or handling.

Disposal

Pro Prep is considered a hazardous material and must be handled as such, in accordance with local, state, and federal regulations. Refer to the Pro Prep Material Safety Data Sheet (MSDS) for additional information, and prior to use or handling.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 9/08