

PA-1021 PLASTIC CEMENT



Commercial Product Data Sheet

Product Description

PA-1021 Plastic Cement is a general purpose roof cement produced from refined asphalt and petroleum solvents with non-asbestos fibers added for reinforcement. PA-1021 is an all-weather grade plastic cement and is specifically formulated to be compatible with Siplast roofing membranes.

Product Uses

PA-1021 Plastic Cement is specially designed for use with guaranteed Siplast Roofing Systems as a mastic for setting all metal flanges and drain lead flashings and for making temporary repairs to the roofing membrane. PA-1021 can also be used as a flashing adhesive on flat or low slope applications, where slumping is not a concern. It is highly flexible, has a trowelling consistency, and may be applied with a trowel or putty knife to dry, clean surfaces.

Product Approvals

PA-1021 Plastic Cement meets or exceeds the requirements of ASTM D 4586 Type II for asbestos free, asphalt based roof cement.

COMMERCIAL PRODUCT INFORMATION

Unit: 5-Gallon Pail
4.7 gallons (17.8 liters) net content

Packaging: The pails are stacked three high on pallets and stretch wrapped.

Pallet: 36 in X 48 in (91 cm X 122 cm) wooden pallet.

Number Pails Per Pallet: 36

Number Pallets Per Truckload: 22

Weight Per Pail: 51 lb (23 kg)

Shipping Classification: White Label (combustible)

Storage and Handling: All containers of PA-1021 Plastic Cement should be stored upright on a clean, flat surface. Care should be taken that containers are not dropped and container seals are not broken prior to use. All containers should be stored in a dry place, out of direct exposure to the elements, and should be kept away from excessive heat, fire or open flames.

Current copies of all Siplast Commercial Product Data Sheets are posted on the Siplast Web site at www.Siplast.com.

Rev 10/07