



MATERIAL SAFETY DATA SHEET

HMIS

H = 2

F = 3

R = 1

PPE = See Section 8

VOC: Max. content less than 50 g/L
(catalyzed)

Section I

Manufacturer: Siplast, an Icopal Group Company
(800) 643-1591 or (800) 922-8800
Address: 1000 E. Rochelle Blvd., Irving, TX 75062-3940
Emergency Phone No.: CHEMTREC, (800) 424-9300 (U.S.), (703) 527-3887 (outside of U.S.)
Product Class: Liquid-applied Waterproofing System - Component
Trade Name: Parapro Flashing Resin (White)

Section II - Ingredients

Ingredient	Percent	ACGIH TLV	OSHA PEL
Methyl methacrylate CAS #80-62-6	15 - 25	50 ppm 205 mg/m ³	100 ppm
2-ethylhexyl acrylate CAS #103-11-7	5 - 12	10 ppm 82 mg/m ³ German MAK	Not Available
Various acrylates CAS #Confidential	8 - 20	Not Established	100 ppm
1,1'-(p-Tolylimino)- dipropan-2-ol CAS #38668-48-3	< 2	Not Available	Not Available
1-Isopropyl-2,2diethyl- trimethylenediisobutyrate CAS #6845-50-0	< 2	Not Available	Not Available
Titanium dioxide CAS #13463-67-7	8 - 12	10 mg/m ³ (total dust)	5 mg/m ³ (total dust)

Crystalline Silica as Quartz has been found to be carcinogenic according to NTP and IARC. This same component is not classified as carcinogenic by OSHA. See Section V.

Section III - Physical Data

Appearance: White
Odor: Typical acrylate odor
Physical state: Liquid
Ignition Point: 536°F (280°C)
Evaporation Rate (Butyl Acetate = 1): Not Established
Vapor Density (Air = 1): Not Established
% Volatile by Volume: Not Established
Solubility in H₂O: Insoluble
Vapor Pressure: Not determined
Viscosity: 38 - 42 dPa*s @20°C
Density: ~ 1.34 g/cm³

Section IV - Fire and Explosion Data

DOT Category: UN1263 Paint
Hazard Class: 3
Label: Flammable
Packaging Group: II
Flash Point: >50°F (10°C)
LEL %: 1.7 UEL %: 8.2 (for methylmethacrylate)
Extinguishing Media: Use foam, carbon dioxide, dry powder, or water spray. Do not use high pressure water. Fight fire from a safe distance due to explosion hazard. Use water spray only to cool containers in fire area.
Special Procedures: Use self-contained breathing apparatus and full protective clothing.

Section V - Health Hazard Data

EMERGENCY AND HAZARDS OVERVIEW:

ROUTES OF ENTRY: Inhalation, skin, and eye contact.

Human Effects and Symptoms of Overexposure:

WARNING! FLAMMABLE.

Harmful if inhaled, swallowed, or absorbed through the skin. Causes skin, eye, and respiratory irritation. May cause skin and respiratory sensitization.

This product contains:

Methyl methacrylate and 2-ethylhexyl acrylate cause skin, eye, and respiratory irritation. High concentrations can cause symptoms of central nervous system depression, such as headache, nausea, dizziness, drowsiness, and confusion.

Both acrylates can cause dermal and respiratory sensitization. Once a person is sensitized, contact with even a small amount may cause outbreaks of dermatitis with symptoms such as skin redness, itching, rash, and swelling. This can spread from the hands or arms to other parts of the body. Persons with respiratory sensitization can experience symptoms of bronchial asthma such as wheezing, difficult breathing, sneezing and runny or blocked nose at low airborne concentrations that have no effect on unsensitized people. IARC has classified 2-ethylhexyl acrylate as class 3, not classifiable as to its carcinogenicity to humans.

Various acrylates, which may cause skin, eye, and respiratory irritation and sensitization.

1,1'-(p-Tolylimino)-dipropan-2-ol which is toxic when ingested or inhaled.

1-Isopropyl-2,2dimethyltrimethylenediisobutyrate, which according to the manufacturer, may cause skin irritation.

Titanium dioxide, may cause mechanical irritation to the eye and respiratory passages and has ACGIH and OSHA exposure limits. However, this product is sold as a liquid preparation and, when used as intended, does not generate dust. Thus the product as such does not pose a respiration hazard attributable to these components. IARC has classified titanium dioxide as class 3, not classifiable as to its carcinogenicity to humans.

Carcinogenicity:

NTP: No

IARC: No

OSHA: No

Emergency and First Aid Procedures:

SKIN: Remove contaminated clothing and shoes. Wash with soap or mild detergent and large amounts of water. Do not use solvents or thinners. Get medical attention if irritation occurs. Wash clothing before reuse.

EYES: Hold eyes open and flush for at least 15 minutes with large amounts of water. Seek medical attention.

INHALATION: Remove to fresh air immediately. If breathing has stopped, give artificial respiration. If breathing is difficult, administer oxygen. Consult physician if irritation of respiratory passage occurs.

INGESTION: Do not induce vomiting. Give two glasses of water to dilute stomach contents. Never give anything by mouth to an unconscious person. Consult a physician immediately.

Section VI - Reactivity Data

Stability: Stable

Hazardous Decomposition Products: Carbon monoxide, carbon dioxide, oxides of nitrogen, hydrocarbon by-products, and black smoke.

Polymerization: Avoid high temperatures. Product may polymerize at > 140°F (60°C). Polymerization is exothermic and may cause container damage and/or fire.

Materials to Avoid: Avoid strong acids, bases, and oxidizing agents to avoid exothermic reactions. Avoid initiators that produce free radicals, and avoid peroxides and metal-ions.

Section VII - Spill or Leak Procedures

Steps to be Taken

Wearing appropriate personal protective equipment, contain spills onto inert absorbent and place in suitable containers.

Disposal Information: Incinerate or dispose of in accordance with Federal, State, or Local regulations.

Waste Disposal Methods: Avoid contamination of ground water or waterways. Do not discharge into sewer system.

Section VIII - Special Protection Information

Respirator: If airborne concentration poses a health hazard, becomes irritating or exceeds recommended limits, use a NIOSH approved respirator in accordance with OSHA Respirator Protection requirements under 29 CFR 1910.134.

Engineering Controls: Use local exhaust ventilation or respiratory protection to maintain employee exposure below TLV.

Skin Protection: Clothing suitable to prevent skin contact. Use butyl rubber gloves and apply barrier creams. Do not use PE or PVC gloves as these materials absorb acrylates. Check suitability recommendations by protective equipment manufacturers, especially toward chemical breakthrough resistance.

Eye: Safety goggles with side shields.

Section IX - Special Precautions

Handling: Do not smoke. Keep away from open fire, flame, or any ignition source. Vapors may form explosive mixtures with air. Avoid skin and eye contact. Avoid breathing fumes. Do not eat, drink, or smoke in application area.

Storage: Store closed containers in cool, dry area away from heat, direct sunlight, oxidizing agents, and strong acids and alkalis. Keep away from open fire, flame, or any ignition source. Keep in well-ventilated areas.

Regulatory Information (Not meant to be all inclusive): All components of this product are on the TSCA Inventory.

This product contains the toxic chemical listed below, which is subject to the supplier notification requirements of Section 313 of the Superfund Amendments and Reauthorization Act (EPCRA/"SARA") and the requirements of 40 CFR Part 372.

<u>PRODUCT</u>	<u>CAS #</u>	<u>MAX %</u>
Methyl methacrylate	80-62-6	25

The information and recommendations contained herein are, to the best of Siplast's knowledge and belief, accurate and reliable as of the date issued. Siplast does not warrant or guarantee their accuracy or reliability, and should not be liable for any loss or damage arising out of the use thereof. User should satisfy himself that he has all current data relevant to his particular use.